

VIBRATION MANAGEMENT CORPORATION

5930 THOMAS ROAD , HOUSTON , TEXAS 77041 , U.S.A

INTERNET ADDRESS: www.vimco.biz

SIZE	17. FL. OZ.
FEATURES	FAST TACK, HIGH STRENGTH
METHYLENE CHLORIDE	NONE
TYPE BOND	TEMPORARY OR PERMANENT
COLOR	TRANSLUCENT
SPRAY PATTERN	FAN-LACE CONTROLLED
MAX. USE TEMPERATURE	130°F
1 SURFACE BONDS (ROOM TEMPERATURE)	15 SECONDS TO 2 HOURS
2 SURFACE BONDS (ROOM TEMPERATURE)	15 SECONDS TO 2 HOURS
INITIAL SHEAR STRENGTH	108
COVERAGE	50 FT ²

APPLICATION INSTRUCTIONS:

SHAKE WELL BEFORE USING. SPRAY 6 TO 8 INCHES FROM SURFACE, KEEPING THE CAN MOVING TO AVOID A BUILD-UP ON THE SURFACE.

Notes / Remarks :	Project :	Title : Engineering Properties : Perimeter Adhesive	Drawing no. S-2600.53
	Client :		
	Consultant :		
	Representative :		