

VIBRATION MANAGEMENT CORPORATION

5930 THOMAS ROAD , HOUSTON , TEXAS 77041 , U.S.A

INTERNET ADDRESS: www.vimco.biz



MODEL	PIPE SIZE (inches)	HANGER ROD DIAMETER (mm)	PIPE DIA RANGE (mm)	MAXIMUM LOAD (uniform radial) (lbs)
PSx-03	3/8	8 / 10	15 - 19	370
PSx-05	1/2	8 / 10	20 - 25	370
PSx-07	3/4	8 / 10	26 - 30	370
PSx-10	1	8 / 10	32 - 36	370
PSx-12	1 1/4	8 / 10	38 - 43	370
PSx-15	1 1/2	8 / 10	47 - 51	370
PSx-17	--	8 / 10	53 - 58	370
PSx-20	2	8 / 10	60 - 64	370
PSx-22	--	8 / 10	68 - 72	370
PSx-25	2 1/2	8 / 10	75 - 80	370
PSx-28	--	8 / 10	81 - 86	370
PSx-30	3	8 / 10	87 - 92	370
PSx-34	--	8 / 10	99 - 105	675
PSx-37	--	8 / 10	107 - 112	675
PSx-40	4	8 / 10	113 - 118	675
PSx-42	--	8 / 10	125 - 130	675
PSx-45	--	8 / 10	132 - 137	675
PSx-50	5	8 / 10	138 - 142	900
PSx-55	--	8 / 10	148 - 152	900
PSx-60	6	8 / 10	159 - 166	900
PSx-67	--	8 / 10	177 - 190	900
PSx-75	--	8 / 10	200 - 212	900
PSx-80	8	8 / 10	215 - 220	900
PSx-100	10	10	269 - 274	900
PSx-120	12	12	320 - 325	900



PSP model

PSL model

MATERIALS

Item	Description
Clamp	Galvanized steel
Lining (on PSL model only)	Synthetic rubber

FEATURES

- * Simple, quick installation.
- * Rubber lining on PSL models absorbs sound and vibration and provides a thermal break.
- * Side bolts with slot and cross-head for ease of tightening

APPLICATION

- * Suspension of non-insulated pipes.

SPECIFICATIONS

- * Underwriters Laboratories Listed in the USA (UL) - 1/2" to 4"

NOTES

1. Choose appropriate model as per requirement:
PSP - Plain , PSL - With rubber lining
2. Pipe size indicated above is for mild steel pipes. Contact factory for copper tube sizing.
3. Options available:
Pipe clamps suitable for 10 / 12mm hanger rods
Nuts for side bolts (standard on PSx-100, Pxs-120)

Notes / Remarks :	Project :	Title : PSP / PSL Extension Split Ring Hanger	Drawing no. S-2730.21
	Client :		
	Consultant :		
	Representative :		
		Rev. 4	